

## PRO Flow M

### PRO Flow M circuit breaker design chart PRO Flow M sulakemitoitustaulukko

				Number of luminaires per circuit breaker Kytettävien valaisimien enimmäismäärä				
				Type	B10 A	B16 A	C10 A	C16 A
PRO Flow M 32-	350	34 W	0,16 A	Type 1a	7	12	10	18
	500	48 W	0,22 A					
	600	57 W	0,26 A					
	700	67 W	0,31 A	Type 1b				
	850	81 W	0,37 A					
	1000	96 W	0,44 A					
PRO Flow M 40-	350	42 W	0,20 A	Type 1b	7	12	10	18
	500	59 W	0,28 A					
	600	71 W	0,32 A					
	700	83 W	0,38 A					
	850	101 W	0,46 A	Type 1c				
	1000	120 W	0,55 A					
	1050	126 W	0,57 A					

Type	Inrush current peak Käynnistysvirtapiikki	Earth leakage current Maavuotovirta
<b>Type 1a</b>	53A, t = 200µs (50 % of I <sub>peak</sub> )	0,12 mA
<b>Type 1b</b>	57A, t = 210µs (50 % of I <sub>peak</sub> )	0,12 mA
<b>Type 1c</b>	62A, t = 330µs (50 % of I <sub>peak</sub> )	0,05 mA